

Perflex MP Series

The **Perflex MP Series** is a high performance thermoplastic elastomers- SEBS (Styrene-Ethylene /Butylene-Styrene) / SBS (Styrene-Butylene-Styrene) copolymer compounding.

Perflex MP Series is the most premium material on the criteria of mechanization-Flexibility and Comfortable.

Applications:

- Toothbrushes
- Consumer article
- Grip

Test method		Hardness	Specific Gravity	Tensile strength	Elongation at break	Tear Strength
Grade name	Color	ASTM 2240	ASTM 792	ASTM 412	ASTM 412	ASTM 746
		Shore A	gm/cm ³	kg/cm ²	%	kg/cm
MP-45NE	Natural	45	1.05	30	650	23
MP-45BE	Black					
MP-65NE	Natural	65	1.05	48	600	35
MP-65BE	Black					
MP-75NE	Natural	75	1.05	58	550	60
MP-75BE	Black					
MP-85NE	Natural	85	1.05	75	520	75
MP-85BE	Black					

Remark: This information may be subject to revision as new knowledge and experience becomes available. The results of our testsare determined by sample check and mean only a technical description of our products. All Information supplied by or on behalf of CP Chemie Resources (M) Sdn Bhd in relationship to its product, whether in nature of data, recommendations or otherwise, is supported by research and believed reliable, but the Company assume no liability whatsoever in respect of application, processing or use made of the aforementioned information and products, or any consequence thereof. This data provided shall not absolve the customer of the responsibility to make test for his intended purpose or process. Therefore, the Company makes no warranties and assumes no liability in connection with any use of this data.

Performance Feature:

- Competitive price with reasonable quality
- BfR, FDA, 2002/72/EC and EN 71/3 conforming
- Adhesion to PP
- Service temperature: -40° C to +80° C
- Halogen-free
- Recyclable



CP Chemie Resources (M) Sdn Bhd (914469-A)

PT 360, Jalan TPP5/1, Taman Perindustrian Puchong, Seksyen 5, 47100 Puchong, Selangor Darul Ehsan, Malaysia.

Tel: +60 (3) 8061 5629 Fax: +60 (3) 8061 5482 www.cpchemie.com info@cpchemie.com